

FD90 Fire Door Product Specification

90-minute fire-resistance range for commercial, residential and public-sector developments.

Classification	FD90
Nominal resistance	90 minutes
Manufacture	Project-specific, CNC-prepared timber fire door products
Supply model	Single orders, phased schedules and large development programmes

Available product options

Door formats	Single leaves, double doorsets and approved project configurations
Glazing	Vision panels and multiple apertures where supported by selected evidence
Finishes	RAL paint, veneer, laminate, primed and paint-grade options
Preparation	Locks, hinges, closers, access control, electric locks and approved hardware
Additional performance	Smoke-control and acoustic options where specified and supported
Bespoke manufacture	Custom dimensions and details subject to technical review

Technical selection requirements

Final leaf thickness, maximum dimensions, frame construction, glazing system, seals, ironmongery and installation details must be confirmed against the applicable fire test, assessment or certification evidence for the selected configuration. Hassock Wood Ltd will review project schedules and drawings before manufacture.

Information required for quotation

1	Door schedule and quantities
2	Required fire rating and smoke-control designation
3	Leaf and frame dimensions
4	Finish, colour and veneer or laminate reference
5	Glazing and vision-panel arrangement
6	Ironmongery and access-control preparation

7

Delivery phases and programme dates

Important: This document is a product-selection and enquiry guide. It is not a fire certificate, declaration of performance or substitute for project-specific technical approval.